## SK60F

## **THERMO-STOVES**

**de manincor** 

mm 680x660xh1450

CE EN -13240 certification





## SK60F


Ceramic tiles white, bordeaux, ground


## STANDARD EQUIPMENT

- above flue ø 150 mm
- safety heat exhaust outfitted for connection to a close circuit
- oven of mm 350x520xh240
- oven features: 1 grid + 1 baking pan
- pump thermostat
- primary air thermostatic regulation
- external flue air









- 1 Out connection 1"1/4 female
- 2 Connection for thermal outflow circuit 1/2" male
- 3 In connection 1"1/4 female
- 4 Connection for thermal outflow tube 1/2" female
- 5 Connection for thermal outflow circuit 1/2" male
- 6 Boiler exhaust 1/2" female
- 7 Pump thermostat

DATA SHEET	
Nominal heat output (max): 17.1 (26.5) kw	Nominal water heat output (max): 13.4 (20.5) kw
Mean content of CO to 13% O2: 0.06 %	Efficiency: 85.5 %
Maximum operating pressure: 2.5 bar	Boiler capacity: 26.5 Lt
Firebox capacity (LxPxH): 33x36x45 cm	Fill opening (LxH): 35x25 cm
Mean flue gas temperature: 205 °C	Flue gas mass flow: 15.2 g/s
Flue depression: mbar 0.12	Net weight/packaging included: kg 360/380